

CCTV PERIPHERALS



- 🌿 4 Pcs - 6 Pcs - 9 Pcs Monitor single screen combiner.
- 🌿 Automatic scan and resolution support.
- 🌿 Dimensions : 47mm x 295 mm, Fanless system
- 🌿 Front Panel : 11 x LED Display (1 input, 9 output, 1 power)
- 🌿 Input : Back Panel 1 x DVI-I /HDMI
- 🌿 Output : Back Panel 9 x DVI /HDMI (single link cable)
- 🌿 1 x DC Power ,1 x RS-232,1 x IR remote controller

- 🌿 1 Channel analog fiber video converter
- 🌿 The clearest image from away via fiber optic cable.
- 🌿 Electronic earnings control, short circuit protection
- 🌿 Automatic optic arrange and definiton
- 🌿 Receiver and sender tx-rx unit RS-485 control



- 🌿 Dc Iris Varifocal Lens (5MP)
- 🌿 Mounting : CS
- 🌿 Light: F1.0
- 🌿 Image Format :1/3"
- 🌿 Image Angle : 97.4° - 18.1°



- ✔ Dc Iris Varifocal Lens (2MP)
- ✔ Mounting : CS
- ✔ Light : F1.6
- ✔ Image Format:1/3"
- ✔ Image Area : 97.4° - 18.1°

- ✔ Dc Iris Varifocal Lens (3MP)
- ✔ Mounting : CS
- ✔ Light: F1.6
- ✔ Image Format :1/3"
- ✔ Image Area: 49.3° - 4.7°



- ✔ CCTV Connection Box





- ✔ Plastic camera stand
- ✔ Indoor
- ✔ Adjustable, plastic material
- ✔ Easy mounting
- ✔ White color

- ✔ Long-Short camera Stand
- ✔ Outdoor
- ✔ Adjustable, iron material
- ✔ Easy mounting
- ✔ Grey color





- ✔ Short camera stand
- ✔ Outdoor
- ✔ Adjustable, iron material
- ✔ Easy mounting holes

- ✔ Camera Stand
- ✔ Outdoor
- ✔ Adjustable, iron material
- ✔ Easy mounting holes
- ✔ Grey color



- ✔ Camera power supply
- ✔ Regulated
- ✔ Indoor
- ✔ DC 12V / 3A

- ✔ Camera power supply
- ✔ Regulated
- ✔ Indoor
- ✔ DC 12V / 3A



- ✔ Camera power suppl
- ✔ DC 12 V / 20A, regulated
- ✔ Iron case,indoor (IP20)
- ✔ Terminal connection
- ✔ Short circuit, overcurrent protection
- ✔ Over temperature (Via Fan)
- ✔ Adjustable output voltage